

Break-away connector kits

- 01 Line side housing (receptacle)
- 02 Crimp-on fuse holder*
- 03 Load side housing (plug)
- 04 Crimp-on fuse holder*
- 05 Line side housing (receptacle)
- 06 Crimp-on fuse holder*
- 07 Crimp-on fuse holder*
- 08 Load side housing (plug)
- 09 Crimp-on fuse holder*
- 10 Crimp-on fuse holder*

Features/benefits:

- Completely waterproof
- Individual fusing allows separation of kit without de-energizing complete circuit
- Break-away style fuse holder eliminates risk of electrical shock
- Exposed current-carrying components are all contained in harmless load side of the kit
- Readily identifiable problem area simplifies maintenance
- Easy to install, no need for tapes or compounds
- Insulated to 600 V

Applications:

- Roadway lighting fixtures
- Flood and area lighting fixtures
- Power distribution systems

Style 65 break-away

Type: Single pole in-line

Electrical rating: For 600 V, 10–30 A, 1³/₃₂ in. x 1¹/₂ in. fuse*

Cat. no.	Conductor size (AWG)	Conductor material	Packaging unit	Packaging standard
65 U	#14–#6	Copper	1	20

*Fuse not included with kit. Do NOT use glass fuses.

Max. overall length, installed, 7¹/₄ in. diameter 1¹/₈ in.



Style D65 break-away

Type: Double pole in-line

Electrical rating: For 600 V, 10–30 amp., 1³/₃₂ in. x 1¹/₂ in. fuse*

Cat. no.	Conductor size (AWG)	Conductor material	Packaging unit
D65 U	#14–#6	Copper	20

*Fuse not included with kit. Do NOT use glass fuses.

Max. overall length, installed, 7¹/₄ in. diameter 2¹/₈ in.

