Features

- Straight Siderail Design: Extruded I-beam
  Nominal Height 4" to 7”
  Loading Height 3" to 6”
- Snap-in splice plate connection.
- Reverse position of every other rung for bottom or top mounting of cable ties.
- Versatile continuous open slot rungs (strut profile).
- Exclusive Ty-Rap cable tie slots (5/8 x 5/8) on one inch (1”) centers.
- Extra wide rung design.
- Four bolt connection.
- Choice of two styles of fitting (U & H) siderails.

Applications

COMMERCIAL
- Schools
- Hospitals
- Office Buildings
- Airports
- Casinos
- Stadiums

INDUSTRIAL
- Petro-Chemical Plants
- Automotive Plants
- Paper Plants
- Food Processing
- Power Plants
- Refineries
- Manufacturing
- Mining

Accessories

- Each pair of splice plates comes with 3/8" mounting hardware.
- Complete line of accessories and support systems.

Material

6063 T6 Aluminum Alloy

Compliance

CSA, NEMA, NEC, UL

Load Ratings

1.5 Safety factor. All tray sections will support an additional 200 lb concentrated load on any portion of tray (siderail, rung, etc.) above and beyond published load class.

T&B aluminum cable tray is composed of two distinct systems H-Style and U-Style. These systems are interchangeable.