


Non-Metallic Boxes

Non-Metallic

NuTek®



WSW-N



WSW



2-WSW



3-WSW



WSW-BX

Technical Specifications

Cat. No.	Width	Capacity (cu. in.)	Cable Entries	Use with
2-3/4" Deep - Non-Gangable - 3-3/4" High				
WSW	2-1/4"	18	4	Non-metallic sheathed cable
WSW-BX	2-1/4"	20	4	AC90-Armoured cable
WSW-N	2-1/4"	18	4	Non-metallic sheathed cable
2-WSW	4"	33	8	Non-metallic sheathed cable
3-WSW	5-3/4"	54	12	Non-metallic sheathed cable



Non-Metallic Boxes

Non-Metallic - Airtight model

NuTek®



F-WSW



2-FWSW



3-FWSW



FWSWBX

Technical Specifications

Cat. No.	Width	Capacity (cu. in.)	Cable Entries	Use with
2-3/4" Deep - Non-Gangable - 3-3/4" High				
F-WSW	2-1/4"	18	4	Non-metallic sheathed cable
WSW-FC*	2-1/4"	18	4	Non-metallic sheathed cable
FWSWBX	2-1/4"	20	4	AC90 - Armoured cable
2-FWSW	4"	33	8	Non-metallic sheathed cable
3-FWSW	5-3/4"	54	12	Non-metallic sheathed cable

*Without sealing

Flanges and cable entry tabs are covered with 100% airtight foam gaskets.



Non-Metallic Boxes

Airtight Model

NuTek®



FWOCT



WOCT



WRD



FWRD

Technical Specifications

Cat. No.	Capacity (cu in)	Cable Entries	Use with
2-3/4" Deep - 3-3/4" High - 4" Wide			
FWOCT*	26	4	Non-metallic sheathed cable
WOCT	26	4	Non-metallic sheathed cable
3" Deep - 4-11/16" High - 4-11/16" Wide			
WRD*	26	4	Non-metallic sheathed cable
FWRD	26	4	Non-metallic sheathed cable

*Flanges and cable entry tabs are covered with 100% airtight foam gaskets.

NOTE: CEC 2006 rule 30-302: 4) Where the weight of a luminaire does not exceed 23 kg (50 lbs), the luminaire shall be permitted to be supported by a ceiling outlet box attached directly to the building structure or by a ceiling outlet box attached to a bar hanger.