

Caractéristiques

- One-piece, heavy-duty construction ready to install right out of the box, no need to break apart and re-assemble, no screws or bolts to drop.
- Installs quickly and securely using one hand, universal bolt head accepts a range of tools
- One size fits EMT, rigid and cable conduit to strut channel
- Parallel hook design keeps conduits and cable square with strut
- Reconfigure cabling and conduit systems without complete disassembly. Remove cables easily without disturbing neighbouring clamps.




Fig. 1

Pipe Clamp


Cat. No.	Material	For EMT/Rigid Conduit Trade size	Outer diameter Cable Range (in.)	Design Load (lbs) safety factor=4	Pieces/ Carton
CPC050	Electro-galv comm. steel	1/2	0.650 - 0.890	200	100
CPC075	Electro-galv comm. steel	3/4	0.860 - 1.110	200	100
CPC100	Electro-galv comm. steel	1	1.100 - 1.400	200	100
CPC125	Electro-galv comm. steel	1-1/4	1.400 - 1.725	200	50
CPC150	Electro-galv comm. steel	1-1/2	1.690 - 1.980	200	50
CPC200	Electro-galv comm. steel	2	1.980 - 2.576	200	50
CPC250	Electro-galv comm. steel	2-1/2	2.576 - 3.060	350	25
CPC300	Electro-galv comm. steel	3	3.060 - 3.626	350	25
CPC350	Electro-galv comm. steel	3-1/2	3.626 - 4.126	350	25
CPC400	Electro-galv comm. steel	4	4.126 - 4.626	350	25

Available in Stainsteel 316L, add suffix SS6.



Steel City® Hangers & Clamps

Strut Accessories



Features

- We offer two pre-assembled pipe clamps that are easy to install.
- Both types of clamps are heavy-duty steel construction and are electrogalvanized.
- Quik Clamp is a true one-piece assembly with no loose parts to be fitted.
- The 703 Universal strap needs some assembly and one size fits both EMT and rigid conduit.




Fig. 1




Fig. 2

Quik Clamp - Rigid Conduit

Cat. Number	Fig. no.	Conduit Size		Material Thickness		Design Load		Wt./C		Std. Pkg.	
		in.	(mm)	Gauge	in.	(mm)	Lb	kN	Lb		kg
QCR1/2EG	1	1/2	(15)	14	0.075	(1.9)	425	1.89	19	8.60	50
QCR3/4EG	1	3/4	(20)	14	0.075	(1.9)	425	1.89	21	9.50	50
QCR1EG	1	1	(25)	14	0.075	(1.9)	425	1.89	22	10.00	50
QCR1-1/4EG	1	1-1/4	(32)	14	0.075	(1.9)	425	1.89	25	11.40	50
QCR1-1/2EG	1	1-1/2	(40)	14	0.075	(1.9)	425	1.89	27	12.30	50
QCR2EG	1	2	(50)	14	0.075	(1.9)	425	1.89	30	13.60	25
QCR2-1/2EG	1	2-1/2	(65)	12	0.105	(2.6)	500	2.22	44	20.00	25
QCR3EG	1	3	(80)	12	0.105	(2.6)	500	2.22	50	22.70	25
QCR3-1/2EG	1	3-1/2	(90)	12	0.105	(2.6)	500	2.22	56	25.50	25
QCR4EG	1	4	(100)	12	0.105	(2.6)	500	2.22	59	26.80	25

Quik Clamp - Thinwall (EMT) Conduit

Cat. Number	Fig. no.	Conduit Size		Material Thickness		Design Load		Wt./C		Std. Pkg.	
		in.	(mm)	Gauge	in.	(mm)	Lb	kN	Lb		kg
QCE1/2EG	1	1/2	(15)	14	0.075	(1.9)	425	1.89	17	7.70	50
QCE3/4EG	1	3/4	(20)	14	0.075	(1.9)	425	1.89	19	8.60	50
QCE1EG	1	1	(25)	14	0.075	(1.9)	425	1.89	20	9.10	50
QCE1-1/4EG	1	1-1/4	(32)	14	0.075	(1.9)	425	1.89	23	10.50	50
QCE1-1/2EG	1	1-1/2	(40)	14	0.075	(1.9)	425	1.89	25	11.40	50
QCE2EG	1	2	(50)	14	0.075	(1.9)	425	1.89	28	12.70	25

703 Universal Straps

Cat. No.	Fig. No.	EMT, Rigid Conduit or Pipe Size	Material	Design Load (lbs.)	Std. Ctn.
703-1/2EG	2	1/2	16 ga.	400	100
703-3/4EG	2	3/4	14 ga.	550	100
703-1EG	2	1	14 ga.	550	100
703-1-1/4EG	2	1-1/4	14 ga.	800	50
703-1-1/2EG	2	1-1/2	14 ga.	800	50
703-2EG	2	2	14 ga.	800	50

See our Superstrut catalogue for a larger variety of pipe and cable clamps.