

Ty-Rap®


Stainless Steel Cable Ties




Mini Stainless Steel Cable Ties



Standard Stainless Steel Cable Ties



Reusable Stainless Steel Cable Ties



Multi-Lok Ties



Free-End Clamps

Specifications

Cat. No.	Width		Length		Thickness		Max. Dia. Single Wrap		Max. Dia. Double Wrap		
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	
SS7-180	.177	4.50	6.5	165	.015	.38	1.7	43	(single wrap)		
SS10-180	.177	4.50	10	254	.015	.38	2.8	71	(single wrap)		
SS16-180	.177	4.50	16	406	.015	.38	4.7	119	(single wrap)		
SS23-180	.177	4.5	22.5	572	.015	.38	6	152	-		
SS29-180	.177	4.5	29.0	737	.015	.38	8	203	-		
SS10-250	1/4	6.35	10	254	.015	.38	2.1	53			
SS17-250	1/4	6.35	16.5	419	.015	.38	4.3	109	(single wrap)		
SS23-250	1/4	6.35	22.5	572	.015	.38	6.5	165	(single wrap)		
SS29-250	1/4	6.35	29	737	.015	.38	8.5	215	(single wrap)		
SS35-250	1/4	6.35	35	889	.015	.38	10.5	265			
SSR6-250C	1/4	6.35	6	152	.015	.38	1.5	38	N.A.	N.A.	
SSR9-250C	1/4	6.35	9	229	.015	.38	2.5	63	1.1	28	
SSR12-250C	1/4	6.35	12	305	.015	.38	3.4	86	1.5	38	
SSR18-250C	1/4	6.35	18	457	.015	.38	5.4	137	2.5	64	
SSR24-250C	1/4	6.35	24	610	.015	.38	7.3	185	3.5	89	
SSR6-375C	3/8	9.53	6	152	.015	.38	1.5	38	N.A.	N.A.	
SSR9-375C	3/8	9.53	9	229	.015	.38	2.5	63	1.1	28	
SSR12-375C	3/8	9.53	12	305	.015	.38	3.4	86	1.5	38	
SSR18-375C	3/8	9.53	18	457	.015	.38	5.4	137	2.5	64	
SSR24-375C	3/8	9.53	24	610	.015	.38	7.3	185	3.5	89	
SSR30-375C	3/8	9.53	30	762	.015	.38	9.1	231	4.4	112	
SSR36-375C	3/8	9.53	36	914	.015	.38	11.0	280	5.3	135	
Uncoated	Nylon 11 Coated										
TYS6-280	TYS6-280C	.28	7.00	6	152	.010	.25	1.9	48		
TYS9-280	TYS9-280C	.28	7.00	9	229	.010	.25	2.8	71		
TYS12-280	TYS12-280C	.28	7.00	12	305	.010	.25	3.8	96		
TYS18-280	TYS18-280C	.28	7.00	18	457	.010	.25	5.7	144	(single wrap)	
TYS24-280	TYS24-280C	.28	7.00	24	610	.010	.25	7.6	193	(single wrap)	
TYS6-470	TYS6-470C	.47	12.00	6	152	.010	.25	1.9	48		
TYS9-470	TYS9-470C	.47	12.00	9	229	.010	.25	2.8	71		
TYS12-470	TYS12-470C	.47	12.00	12	305	.010	.25	3.8	96		
TYS18-470	TYS18-470C	.47	12.00	18	457	.010	.25	5.7	144		
TYS24-470	TYS24-470C	.47	12.00	24	610	.010	.25	7.6	193		
SSH10-250		1/4	6.35	10	250	.020	.51	2.0	50	N.A.	N.A.
SSH16-250		1/4	6.35	16	400	.020	.51	3.5	88	1.5	38
SSH19-250		1/4	6.35	19	480	.020	.51	5.0	127	2.5	63
SSH27-250		1/4	6.35	27	680	.020	.51	7.0	177	3.5	88
SSH34-250		1/4	6.35	34	860	.020	.51	9.0	228	4.5	114
SSH16-375		3/8	9.53	16	400	.025	.63	3.5	88	1.5	38
SSH44-375		3/8	9.53	44	1120	.025	.63	12.0	304	6.0	152
SSH18-500		1/2	12.70	18	460	.030	.76	4.0	101	2.0	50
SSH31-500		1/2	12.70	31	780	.030	.76	8.0	203	4.0	101
SSH21-625		5/8	15.88	21	530	.030	.76	5.0	127	2.5	63
SSH56-625		5/8	15.88	56	1420	.030	.76	16.0	406	8.0	203
SSH69-625		5/8	15.88	69	1750	.030	.76	20.0	508	10.0	254
SSH24-750		3/4	19.05	24	600	.030	.76	6.0	152	3.0	76
SSH37-750		3/4	19.05	37	940	.030	.76	10.0	254	5.0	127
SSH50-750		3/4	19.05	50	1270	.030	.76	14.0	355	7.0	177
SSH62-750		3/4	19.05	62	1570	.030	.76	18.0	457	9.0	228



Specifications—continued

Cat. No.	Stainless Steel Type	Coating or Finish	Min. Loop Tensile Strength Single Wrap		Min. Loop Tensile Strength Double Wrap		Application Tools Used	General Application
			Lb.	Newtons	Lb.	Newtons		
SS7-180*	304	Dull to Bright	100	445	(single		<ul style="list-style-type: none"> • Wire/Cable bundling • I.D. Tagging 	
SS10-180*	304		100	445	wrap	WTA290 WT5S DAS-250		
SS16-180*	304		100	445	only)			
SS23-180*	304		100	445				
SS29-180*	304		100	445				
SS10-250*	304	Dull to Bright	200	890	(single		WTA250 WT5S DAs-250	<ul style="list-style-type: none"> • Wire/Cable bundling • I.D. Tagging
SS17-250*	304		200	890	wrap			
SS23-250*	304		200	890	only)			
SS29-250*	304		200	890				
SS35-250*	304		200	890				
SSR6-250C	200/300		75	334	300	1334	WTAE200 WTAE201 WTC075	<ul style="list-style-type: none"> • Reusable • Cable bundling • Oil Rigs • Tele-Communications towers • Hazardous and corrosive environments
SSR9-250C	200/300		75	334	300	1334		
SSR12-250C	200/300		75	334	300	1334		
SSR18-250C	200/300	Nylon 11 Coated	75	334	300	1334		
SSR24-250C	200/300	(Uncoated or other	75	334	300	1334		
SSR6-375C	200/300	colours available on	100	445	500	2224		
SSR9-375C	200/300	special order)	100	445	500	2224		
SSR12-375C	200/300		100	445	500	2224		
SSR18-375C	200/300		100	445	500	2224		
SSR24-375C	200/300		100	445	500	2224		
SSR30-375C	200/300		100	445	500	2224		
SSR36-375C	200/300		100	445	500	2224		
Uncoated	Nylon 11 Coated							
TYS6-280	TYS6-280C	316	250	1112				
TYS9-280	TYS9-280C	316	250	1112				
TYS12-280	TYS12-280C	316	250	1112				
TYS18-280	TYS18-280C	316	250	1112	(single			
TYS24-280	TYS24-280C	316	250	1112	wrap			
TYS6-470	TYS6-470C	316	250	1112	only)			
TYS9-470	TYS9-470C	316	250	1112				
TYS12-470	TYS12-470C	316	250	1112				
TYS18-470	TYS18-470C	316	250	1112				
TYS24-470	TYS24-470C	316	250	1112				
SSH10-250		201	450	2002	1200	5338	WTC001 WTC075 WTJ020	<ul style="list-style-type: none"> • Indus. hoses • Cable bundling • Hi-strength
SSH16-250		201	450	2002	1200	5338		
SSH19-250		201	450	2002	1200	5338		
SSH27-250		201	450	2002	1200	5338		
SSH34-250		201	450	2002	1200	5338		
SSH16-375		201	900	4003	2400	10675		
SSH44-375		201	900	4003	2400	10675		
SSH18-500		201	1400	6227	3300	14678		
SSH31-500		201	1400	6227	3300	14678		
SSH21-625		201	1700	7562	4000	17792		
SSH56-625		201	1700	7562	4000	17792		
SSH69-625		201	1700	7562	4000	17792		
SSH24-750		201	2000	8896	5000	22240		
SSH37-750		201	2000	8896	5000	22240		
SSH50-750		201	2000	8896	5000	22240		
SSH62-750		201	2000	8896	5000	22240		

Thomas & Betts Stainless Steel Cable Ties have passed a variety of mechanical, environmental, and electrical tests. Other data can be made available upon request.


*S.S. series also available in (316) Stainless.

Ty-Rap®

Stainless Steel Cable Ties



Stainless steel cable ties have been designed for high-temperature applications as in boiler rooms, and for use in areas of harsh, corrosive environments such as shipyards and off-shore oil platforms. They are made of type 316 stainless steel, and rated at 200 pound tensile strength. Smooth edges protect both the cable insulation and the installer.



WT3S

Stainless Steel Cable Ties

Cat. No.	Body Width (in.)	Length (in.)	Max. Wire Bundle Dia. (in.)	Tensile Strength (lb.)	Std. Pkg.
TYS8	.310	10.65	2	200	100
TYS14	.310	14.65	4	200	50
TYS22	.310	22.65	6	200	50
TYS28	.310	28.65	8	200	50

Note: Use WT3S Tool for tensioning and cutoff.

- Cannot be coated with any covering material.

Stainless Steel Strap on a Reel

Cat. No.	Description	Body Width (in.)	Tensile Strength (lb.)	Std. Pkg.
TYS1000	1000 foot of strap, 2 reels of 500 feet each	.310	200	1

Stainless steel ties of virtually any length can be produced from the 1000 foot reel in combination with the matching head.

Note: Use WT3S tool for tensioning and cutoff.

Stainless Steel Locking Heads

Cat. No.	Description	Std. Pkg.
TYS5200H	Heads only for stainless steel strap	50

Stainless Steel Mounting Base

Cat. No.	Description	Std. Pkg.
TCS25	Mounting base for stainless steel ties	50

Ty-Rap® Stainless Steel Tool

Cat. No.	Description	Std. Pkg.	Wt. Each
WT3S	Stainless steel cable tie installing tool. TYS body slots	1	8 oz.

Tool is designed to install tie. Do not attempt to cut excess strap with tool.