




Wire Protection Products




Spiral Wrap

- For protection of bundles from .063" to 7".
- Install gapped for greater flexibility or butted for maximum abrasion resistance, insulation and rigidity.
- Stocked in 3 materials including Polyethylene and 6/6 Nylon.
- a.k.a.: Reverse cut, left-hand cut, counter clockwise cut.
- Use cutting tool SR-100.



Cat. No.	Material	Outside Diameter		Pitch		Nominal Wall Thickness		Min./Max. Bundle Range				UL Flammability	
		Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)		
SRPE-125-9-C	Natural Polyethylene	.125	(3.2)	.210	(5.3)	.035	(0.9)	.063	(1.6)	to	0.500	(12.7)	94 HB
SRPE-187-9-C	Natural Polyethylene	.187	(4.8)	.240	(6.1)	.040	(1.0)	.125	(3.2)	to	1.500	(25.9)	94 HB
SRPE-250-9-C	Natural Polyethylene	.250	(6.4)	.375	(9.5)	.045	(1.1)	.188	(4.8)	to	2.000	(50.8)	94 HB
SRPE-375-9-C	Natural Polyethylene	.375	(9.5)	.438	(11.1)	.052	(1.3)	.313	(7.9)	to	3.000	(76.2)	94 HB
SRPE-500-9-C	Natural Polyethylene	.500	(12.7)	.563	(14.3)	.062	(1.6)	.375	(9.5)	to	4.000	(102.0)	94 HB
SRPE-625-9-C	Natural Polyethylene	.625	(15.9)	.625	(15.9)			.625	(15.9)	to	4.500	(114.3)	94 HB
SRPE-750-9-C	Natural Polyethylene	.750	(19.1)	.750	(19.1)	.065	(1.7)	.750	(19.1)	to	5.000	(127.0)	94 HB
SRPE-1000-9-C	Natural Polyethylene	1.000	(25.4)	1.110	(28.2)	.070	(1.8)	1.000	(25.4)	to	7.000	(177.8)	94 HB
SRPE-125-0-C	UV Black Polyethylene	.125	(3.2)	.210	(5.3)	.035	(0.9)	.063	(1.6)	to	0.500	(12.7)	94 HB
SRPE-187-0-C	UV Black Polyethylene	.187	(4.8)	.240	(6.1)	.040	(1.0)	.125	(3.2)	to	1.500	(25.9)	94 HB
SRPE-250-0-C	UV Black Polyethylene	.250	(6.4)	.375	(9.5)	.045	(1.1)	.188	(4.8)	to	2.000	(50.8)	94 HB
SRPE-375-0-C	UV Black Polyethylene	.375	(9.5)	.438	(11.1)	.052	(1.3)	.313	(7.9)	to	3.000	(76.2)	94 HB
SRPE-500-0-C	UV Black Polyethylene	.500	(12.7)	.563	(14.3)	.062	(1.6)	.375	(9.5)	to	4.000	(102.0)	94 HB
SRPE-625-0-C	UV Black Polyethylene	.625	(15.9)	.625	(15.9)			.625	(15.9)	to	4.500	(114.3)	94 HB
SRPE-750-0-C	UV Black Polyethylene	.750	(19.1)	.750	(19.1)	.065	(1.7)	.750	(19.1)	to	5.000	(127.0)	94 HB
SRPE-1000-0-C	UV Black Polyethylene	1.000	(25.4)	1.110	(28.2)	.070	(1.8)	1.000	(25.4)	to	7.000	(177.8)	94 HB
SRNY-250-9-C	Natural Nylon 6/6	.250	(6.4)	.375	(9.5)	.025	(.6)	.187	(4.8)	to	2.000	(50.8)	94 HB
SRNY-375-9-C	Natural Nylon 6/6	.375	(9.5)	.438	(11.1)			.312	(7.9)	to	3.000	(76.2)	94 HB
SRNY-500-9-C	Natural Nylon 6/6	.500	(12.7)	.563	(14.3)	.035	(.9)	.375	(9.5)	to	4.000	(102.0)	94 HB
SRTL-250-WH-C	*Teflon®	.250	(6.4)	.375	(9.5)	.030	(.76)	.188	(4.8)	to	2.000	(50.8)	94 V-0
SRTL-375-WH-C	*Teflon®	.375	(9.5)	.438	(11.1)	.030	(.76)	.313	(7.9)	to	3.000	(76.2)	94 V-0
SRTL-500-WH-C	*Teflon®	.500	(12.7)	.563	(14.3)	.030	(.76)	.375	(9.5)	to	4.000	(102.0)	94 V-0
SRTL-625-WH-C	*Teflon®	.625	(15.9)	.625	(15.9)	.030	(.76)	.625	(15.9)	to	4.500	(114.3)	94 V-0
SRTL-750-WH-C	*Teflon®	.750	(19.1)	.750	(19.1)	.030	(.76)	.750	(19.1)	to	5.000	(127.0)	94 V-0
Tolerance ±		.030	(.762)		.010	(.254)							

• Stocked in 100 foot rolls.



SR-100 Cutting Tool

Use our SR-100 cutting tool for all your plastic pipe and PVC conduit needs to 1 1/4" I.D.

Features:


- High-carbon, *Teflon®-coated replacement steel blade.

- Contoured handle resists tube crushing.
- Produces no "sawdust", no need to debur.
- Lightweight, low-profile and no exposed blade when stored.

*Teflon® is a trademark of E.I. DuPont de Nemours and Company.



Cat. No.	Description
SR-100	Cutting Tool
SR-R	Replacement Blade

Wire Protection Products



Forward Cut Spiral Wrap

- For protection of bundles from .063" to 7".
- Install gapped for greater flexibility or butted for maximum abrasion resistance, insulation and rigidity.
- Available in 4 materials including Polyethylene, Nylon and Teflon®.
- a.k.a.: Right-hand cut, clockwise cut.
- Use cutting tool SR-100.



Cat. No.	Material	Outside Diameter		Pitch		Nominal Wall Thickness		Min./Max. Bundle Range				UL Flammability	
		Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)		
SRPE-250F-9-C	Natural Polyethylene	.250	(6.4)	.375	(9.5)	.045	(1.1)	.188	(4.8)	to	2.000	(50.8)	94 HB
SRPE-187F-9-C	Natural Polyethylene	.187	(4.8)	.240	(6.1)	.040	(1.0)	.125	(3.2)	to	1.500	(25.9)	94 HB
SRPE-250F-9-C	Natural Polyethylene	.250	(6.4)	.375	(9.5)	.045	(1.1)	.188	(4.8)	to	2.000	(50.8)	94 HB
SRPE-375F-9-C	Natural Polyethylene	.375	(9.5)	.438	(11.1)	.052	(1.3)	.313	(7.9)	to	3.000	(76.2)	94 HB
SRPE-500F-9-C	Natural Polyethylene	.500	(12.7)	.563	(14.3)	.062	(1.6)	.375	(9.5)	to	4.000	(102.0)	94 HB
SRPE-625F-9-C	Natural Polyethylene	.625	(15.9)	.625	(15.9)	.062	(1.6)	.625	(15.9)	to	4.500	(114.3)	94 HB
SRPE-750F-9-C	Natural Polyethylene	.750	(19.1)	.750	(19.1)	.065	(1.7)	.750	(19.1)	to	5.000	(127.0)	94 HB
SRPE-1000F-9-C	Natural Polyethylene	1.000	(25.4)	1.110	(28.2)	.070	(1.8)	1.000	(25.4)	to	7.000	(177.8)	94 HB
SRPE-187F-0-C	UV Black Polyethylene	.187	(4.8)	.240	(6.1)	.040	(1.0)	.125	(3.2)	to	1.500	(25.9)	94 HB
SRPE-250F-0-C	UV Black Polyethylene	.250	(6.4)	.375	(9.5)	.045	(1.1)	.188	(4.8)	to	2.000	(50.8)	94 HB
SRPE-375F-0-C	UV Black Polyethylene	.375	(9.5)	.438	(11.1)	.052	(1.3)	.313	(7.9)	to	3.000	(76.2)	94 HB
SRPE-500F-0-C	UV Black Polyethylene	.500	(12.7)	.563	(14.3)	.062	(1.6)	.375	(9.5)	to	4.000	(102.0)	94 HB
SRPE-625F-0-C	UV Black Polyethylene	.625	(15.9)	.625	(15.9)	.062	(1.6)	.625	(15.9)	to	4.500	(114.3)	94 HB
SRPE-750F-0-C	UV Black Polyethylene	.750	(19.1)	.750	(19.1)	.065	(1.7)	.750	(19.1)	to	5.000	(127.0)	94 HB
SRPE-1000F-0-C	UV Black Polyethylene	1.000	(25.4)	1.110	(28.2)	.070	(1.8)	1.000	(25.4)	to	7.000	(177.8)	94 HB
SRFR-187F-WH-C	White Flame Retardant Polyethylene	.187	(4.8)	.240	(6.1)	.040	(1.0)	.125	(3.2)	to	1.500	(25.9)	94 V-0
SRFR-250F-WH-C	White Flame Retardant Polyethylene	.250	(6.4)	.375	(9.5)	.045	(1.1)	.188	(4.8)	to	2.000	(50.8)	94 V-0
SRFR-375F-WH-C	White Flame Retardant Polyethylene	.375	(9.5)	.438	(11.1)	.052	(1.3)	.313	(7.9)	to	3.000	(76.2)	94 V-0
SRFR-500F-WH-C	White Flame Retardant Polyethylene	.500	(12.7)	.563	(14.3)	.062	(1.6)	.375	(9.5)	to	4.000	(102.0)	94 V-0
SRTL-250-F-9-C	*Teflon®	.250	(6.4)	.375	(9.5)	.030	(.76)	.188	(4.8)	to	2.000	(50.8)	94 V-0
SRTL-375-F-9-C	*Teflon®	.375	(9.5)	.438	(11.1)	.030	(.76)	.313	(7.9)	to	3.000	(76.2)	94 V-0
SRTL-500-F-9-C	*Teflon®	.500	(12.7)	.563	(14.3)	.030	(.76)	.375	(9.5)	to	4.000	(102.0)	94 V-0
SRTL-625-F-9-C	*Teflon®	.625	(15.9)	.625	(15.9)	.030	(.76)	.625	(15.9)	to	4.500	(114.3)	94 V-0
SRTL-750-F-9-C	*Teflon®	.750	(19.1)	.750	(19.1)	.030	(.76)	.750	(19.1)	to	5.000	(127.0)	94 V-0
Tolerance ±		.030	(.762)	.010	(.254)								

• Stocked in 100 foot rolls.

*Teflon® is a trademark of E.I. DuPont de Nemours and Company.

Polyethylene

For general indoor use to 122°F. Wrap is flexible and easy to work with.

UV Polyethylene

Available in black only. Designed to resist ultraviolet light in outdoor applications.

*TEFLON®

PTFE Flexible Industrial Tubing meets or exceeds ASTM D 3295. 260°C -240°C


Flame Retardant Polyethylene

Material is UL rated 94 V-0. More economical and less rigid than nylon.

Nylon 6/6

Offers highest abrasion resistance and rigidity. Self-extinguishing to UL 94 HB and a Recognized Component.



Wire Protection Products



Molded Grommeting


- Meets MS21266-(1-4)N.
- Available in 3 materials for panel thicknesses from .015" to .192".

- Grommet is used to protect panel edges and knock-outs where the chafing of passing wires is a concern.
- Suitable for round hole or odd shape applications.
- Also Available in Fluoropolymer.




Cat. No.	Material	A		B		C		D		For Panel Thickness	Military Standard Numbers	Per Pkg.
		Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)			
GSNY-052-9-C	Natural Nylon	.150	(3.81)	.056	(1.42)					.015 (.381) to .052 (1.32)	MS-21266-1N	100
GSNY-085-9-C	Natural Nylon	.175	(4.44)	.090	(2.28)	.155	(3.93)	.100	(2.54)	.053 (1.34) to .085 (2.15)	MS-21266-2N	100
GSNY-128-9-C	Natural Nylon	.220	(5.58)	.131	(3.32)					.086 (2.18) to .128 (3.25)	MS-21266-3N	100
GSNY-192-9-C	Natural Nylon	.323	(8.20)	.192	(4.88)	.230	(5.84)	.162	(4.12)	.128 (3.25) to .192 (4.88)	MS-21266-4N	100
GSTZ-052-9-C	Natural Fluoropolymer	.150	(3.81)	.045	(1.42)					.015 (.381) to .052 (1.32)	-	100
GSTZ-085-9-C	Natural Fluoropolymer	.175	(4.44)	.090	(2.28)	.155	(3.93)	.100	(2.54)	.053 (1.34) to .085 (2.15)	-	100
GSTZ-128-9-C	Natural Fluoropolymer	.220	(5.58)	.131	(3.32)					.086 (2.18) to .128 (3.25)	-	100
GSTZ-192-9-C	Natural Fluoropolymer	.323	(8.20)	.192	(4.88)	.230	(5.84)	.162	(4.12)	.128 (3.25) to .192 (4.88)	-	100
Tolerance		+.015 -.005		(+.381 -.127)		+.020 -.005		(+.508 -.127)				

Wire Protection Products



Extruded Grommeting

- Used to line panel edges and knock-outs where the chafing of passing wires is a concern.



- Available in 8 stock sizes in 100 foot lengths for panels from .030" to .250" thick.
- A variety of stocked materials to cover a wide range of applications.
- Un-cut Polyethylene is ideal for protection of glass, sheet metal, wood panels or other sheet-form materials.
- In most applications, grommeting will grip tightly by itself. If not, a touch of epoxy will keep it in place.

Cat. No.	Material	A		C		D		E		UL Flammability
		Max. Panel Thickness Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)	
GRNY-040-9-C	Natural Nylon	.040	(1.01)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 V-2
GRNY-052-9-C	Natural Nylon	.052	(1.32)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 V-2
GRNY-062-9-C	Natural Nylon	.062	(1.57)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 V-2
GRNY-085-9-C	Natural Nylon	.085	(2.15)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 V-2
GRNY-100-9-C	Natural Nylon	.100	(2.54)	.045	(1.14)	.220	(5.58)	.210	(5.33)	94 V-2
GRNY-125-9-C	Natural Nylon	.125	(3.17)	.050	(1.27)	.220	(5.58)	.205	(5.23)	94 V-2
GRNY-187-9-C	Natural Nylon	.187	(4.74)	.050	(1.27)	.270	(6.85)	.275	(6.98)	94 V-2
GRNY-250-9-C	Natural Nylon	.250	(6.35)	.050	(1.27)	.280	(7.11)	.370	(9.39)	94 V-2
GRNY-040-0-C	Black Nylon	.040	(1.01)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 V-2
GRNY-052-0-C	Black Nylon	.052	(1.32)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 V-2
GRNY-062-0-C	Black Nylon	.062	(1.57)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 V-2
GRNY-085-0-C	Black Nylon	.085	(2.15)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 V-2
GRNY-100-0-C	Black Nylon	.100	(2.54)	.045	(1.14)	.220	(5.58)	.210	(5.33)	94 V-2
GRNY-125-0-C	Black Nylon	.125	(3.17)	.050	(1.27)	.220	(5.58)	.205	(5.23)	94 V-2
GRNY-187-0-C	Black Nylon	.187	(4.74)	.050	(1.27)	.270	(6.85)	.275	(6.98)	94 V-2
GRNY-250-0-C	Black Nylon	.250	(6.35)	.050	(1.27)	.280	(7.11)	.370	(9.39)	94 V-2
GRPE-040-9-C	Natural Polyethylene	.040	(1.01)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 HB
GRPE-052-9-C	Natural Polyethylene	.052	(1.32)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 HB
GRPE-062-9-C	Natural Polyethylene	.062	(1.57)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 HB
GRPE-085-9-C	Natural Polyethylene	.085	(2.15)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 HB
GRPE-100-9-C	Natural Polyethylene	.100	(2.54)	.045	(1.14)	.220	(5.58)	.210	(5.33)	94 HB
GRPE-125-9-C	Natural Polyethylene	.125	(3.17)	.050	(1.27)	.220	(5.58)	.205	(5.23)	94 HB
GRPE-187-9-C	Natural Polyethylene	.187	(4.74)	.050	(1.27)	.270	(6.85)	.275	(6.98)	94 HB
GRPE-250-9-C	Natural Polyethylene	.250	(6.35)	.050	(1.27)	.280	(7.11)	.370	(9.39)	94 HB
GRUPE-040-9-C	Un-Cut Polyethylene	.040	(1.01)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 HB
GRUPE-052-9-C	Un-Cut Polyethylene	.052	(1.32)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 HB
GRUPE-062-9-C	Un-Cut Polyethylene	.062	(1.57)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 HB
GRUPE-085-9-C	Un-Cut Polyethylene	.085	(2.15)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 HB
GRUPE-100-9-C	Un-Cut Polyethylene	.100	(2.54)	.045	(1.14)	.220	(5.58)	.210	(5.33)	94 HB
GRUPE-125-9-C	Un-Cut Polyethylene	.125	(3.17)	.050	(1.27)	.220	(5.58)	.205	(5.23)	94 HB
GRUPE-187-9-C	Un-Cut Polyethylene	.187	(4.74)	.050	(1.27)	.270	(6.85)	.275	(6.98)	94 HB
GRUPE-250-9-C	Un-Cut Polyethylene	.250	(6.35)	.050	(1.27)	.280	(7.11)	.370	(9.39)	94 HB
GRFR-040-WH-C	Flame Retardant Polyethylene	.040	(1.01)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 V-0
GRFR-052-WH-C	Flame Retardant Polyethylene	.052	(1.32)	.040	(1.01)	.190	(4.82)	.125	(3.17)	94 V-0
GRFR-062-WH-C	Flame Retardant Polyethylene	.062	(1.57)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 V-0
GRFR-085-WH-C	Flame Retardant Polyethylene	.085	(2.15)	.045	(1.14)	.200	(5.08)	.170	(4.32)	94 V-0
GRFR-100-WH-C	Flame Retardant Polyethylene	.100	(2.54)	.045	(1.14)	.220	(5.58)	.232	(5.33)	94 V-0
GRFR-125-WH-C	Flame Retardant Polyethylene	.125	(3.17)	.050	(1.27)	.220	(5.58)	.232	(5.32)	94 V-0
GRFR-187-WH-C	Flame Retardant Polyethylene	.187	(4.74)	.050	(1.27)	.270	(6.85)	.275	(6.98)	94 V-0
GRFR-250-WH-C	Flame Retardant Polyethylene	.250	(6.35)	.050	(1.27)	.280	(7.11)	.370	(9.39)	94 V-0
Tolerance		+ .000 - .015	(+ .000) (- .381)	± .007	(.178)	± .010	(.254)	+ .015 - .000	(+ .381) (- .000)	

• 100 feet per roll.