

**Beam Clamps**


**SECTION 4**

**Beam Clamps for Mounting Pipe and Conduit**

**U571**

**U572**

**Conduit Clamp**



For attaching 1/2" thru 1-1/2" conduit to beam, channel, angle or column. Secures conduit to the support parallel or at right angles to it.


5/16" set screw  
12 gauge material

**Standard Finish - GoldGalv®**

Wt./C 38 lb


Cat. No.	Conduit Size	Max. Flange Thickness	Dim. A	Wt./C lb
<b>U571</b>	1/2	1	1-3/4	36
	3/4	3/4	1-3/4	36
	1	1/2	1-3/4	36
<b>U572</b>	3/4	1-1/2	2-1/2	59
	1	1-1/4	2-1/2	59
	1-1/4	1	2-1/2	59
	1-1/2	5/8	2-1/2	59

**Pipe Supports**




**Type RC and RCS**

- Malleable Iron
- For mounting pipe or conduit at right angles to the beam
- Use SS316 suffix for 316 Stainless Steel
- Use HDG suffix for Hot-Dipped Galvanized



**Type EC**

- Malleable Iron
- For mounting pipe or conduit vertically across the beam
- Use HDG suffix for Hot-Dipped Galvanized
- CSA Certified



**Type PC**

- Malleable Iron
- For mounting pipe or conduit parallel to the beam
- Use SS316 suffix for 316 Stainless Steel
- Use HDG suffix for Hot-Dipped Galvanized

Cat No. & Size	Dimensions in inches			Wt./C lb
	O.D. of Conduit or Pipe	Nom. Conduit or Pipe Size	Std. Ctn.	
<b>RCS-3/8</b>	.675	3/8	50	31
<b>RCS-1/2</b>	.840	1/2	50	34
<b>RCS-3/4</b>	1.050	3/4	50	39
<b>RCS-1</b>	1.315	1	50	42
<b>RCS-1-1/4</b>	1.660	1-1/4	50	43
<b>RCS-1-1/2</b>	1.900	1-1/2	50	60
<b>RCS-2</b>	2.375	2	50	72
<b>RC-1/2</b>	.840	1/2	50	36
<b>RC-3/4</b>	1.050	3/4	50	43
<b>RC-1</b>	1.315	1	50	49
<b>RC-1-1/4</b>	1.660	1-1/4	50	51
<b>RC-1-1/2</b>	1.900	1-1/2	50	54
<b>RC-2-SC</b>	2.375	2	50	76
<b>RC-2-1/2</b>	2.875	2-1/2	25	107
<b>RC-3</b>	3.500	3	25	116
<b>RC-3-1/2</b>	4.000	3-1/2	25	134
<b>RC-4-SC</b>	4.500	4	20	158
<b>EC-1/2</b>	.840	1/2	50	69
<b>EC-3/4</b>	1.050	3/4	50	78
<b>EC-1</b>	1.315	1	25	83
<b>EC-1-1/4</b>	1.660	1-1/4	25	108
<b>EC-1-1/2</b>	1.900	1-1/2	25	112
<b>EC-2</b>	2.375	2	25	140
<b>EC-2-1/2</b>	2.875	2-1/2	10	183
<b>EC-3</b>	3.500	3	10	203
<b>PC-3/8</b>	.675	3/8	50	32
<b>PC-1/2</b>	.840	1/2	50	53
<b>PC-3/4</b>	1.050	3/4	50	53
<b>PC-1</b>	1.315	1	50	61
<b>PC-1-1/4</b>	1.660	1-1/4	25	79
<b>PC-1-1/2</b>	1.900	1-1/2	25	56
<b>PC-2</b>	2.375	2	25	116
<b>PC-2-1/2</b>	2.875	2-1/2	25	148
<b>PC-3</b>	3.500	3	10	175
<b>PC-3-1/2</b>	4.00	3-1/2	10	199
<b>PC-4</b>	4.500	4	10	224

**Pipe Supports**

Three types of pipe clamps are available to provide right angle, vertical and parallel attachment to a beam. Types RC, EC and PC are malleable iron clamps with an edge that grips the structural member for maximum holding power when tightened.

Type RCS clamps are all steel, providing two bearing surfaces for strong attachment for mounting pipe or conduit at right angles to the beam.

All parts are electrogalvanized (no suffix) including the threads. The clamps are designed for clamping to a wide variety of beam thicknesses and tapers. Can be installed using only a wrench.