



- All couplings are coated with a nominal .002" (2 mil) blue urethane on the interior.
- A minimum .040" (40 mil) PVC coating is bonded to the exterior.
- Couplings have straight threads, not tapered.
- Molded ribs on outer coating.
- Couplings have pressure-sealing sleeves to protect the connection.

OCAL-BLUE Couplings

PREFIX	Coupling Size Inches Metric Size Designator*	Minimum Length of Metal Inches Millimeters	Total Minimum Length Including Sleeve Inches Millimeters	Weight in Pounds Kilograms
CPL	1/2 16	1.500 38.1	3.7500 95.25	0.13 .058
CPL	3/4 21	1.532 38.91	3.7500 95.25	0.19 0.85
CPL	1 27	1.906 48.41	4.9375 139.70	0.33 .148
CPL	1-1/4 35	1.906 48.41	5.5000 139.70	0.43 .193
CPL	1-1/2 41	1.906 48.41	5.7500 146.05	0.56 .252
CPL	2 53	1.937 49.19	5.9370 150.79	0.77 .346
CPL	2-1/2 63	2.878 73.10	6.8780 174.70	1.85 .832
CPL	3 78	3.031 76.98	7.0310 178.58	2.70 1.215
CPL	3-1/2 91	3.094 78.58	7.0940 180.18	3.78 1.701
CPL	4 103	3.188 80.97	7.1880 182.57	3.08 1.386
CPL	5 129	3.374 85.69	7.3740 187.29	5.00 2.250
CPL	6 155	3.437 87.29	7.4370 188.89	8.00 3.600

NOTE – Inches and Pounds indicated in bold face type
 Metric measure is directly below bold face type
 *Metric size designator (ANSI C80.1-1994).

Item	Size	Material	Color
CPL	3/4	—	-G
		SA = Aluminum Blank = Steel	-G = Gray -R = Red -W = White -B = Blue * Custom Colors Available