


Connectors for Copper Conductors

Two-Way Metric Splice Connectors

Color-Keyed® metric splice connectors are designed for joining low voltage conductors.

Made of electrolytic copper tube having similar dimensions to the Color-Keyed® metric lugs, these connectors are also annealed and electrolytically tin plated.

They feature an internal chamfer at both ends. For easy insertion of the conductor, a center stop is provided to ensure correct positioning.



C o m p r e s s i o n

CAT. NO.	Cond. Size SQMM		Dimensions (mm)		Std. Pkg.	6 Ton TBM62BSCR (Crimps)	14 Ton BPLT14BSCRI (Crimps)	26 Ton TBM26MCC (Crimps)	60 Ton TBM60MCC (Crimps)
	Low Stranded	Flexible	Ø1	L					
MCST1	0.25÷1.5	0.25÷1.5	1.8	15	100	N/A	N/A	N/A	N/A
MCST2	1.5÷2.5	1.5÷2.5	2.4	15	100	N/A	N/A	N/A	N/A
MCST6	4÷6	4÷6	3.6	22	100	MCD6-6 (1+1)	N/A	N/A	N/A
MCST10	10	10	4.6	25	100	MCD10-6 (1+1)	MCD10-14 (1+1)	N/A	N/A
MCST16	16	16	5.8	27	100	MCD16-6 (1+1)	MCD16-14 (1+1)	N/A	N/A
MCST25	25	25	7.0	29	100	MCD25-6 (1+1)	MCD25-14 (1+1)	N/A	N/A
MCST35	35	25÷35	8.9	332	100	MCD35-6 (1+1)	MCD35-14 (1+1)	N/A	N/A
MCST50	50	35÷50	10.0	37	50	MCD50-6 (2+2)	MCD50-14 (1+1)	N/A	N/A
MCST70	70	50÷70	11.3	39	50	MCD70-6 (2+2)	MCD70-14 (1+1)	N/A	N/A
MCST95	95	70÷95	13.5	43	25	MCD95-6 (2+2)	MCD95-14 (1+1)	N/A	N/A
MCST120	120	95÷120	15.2	47	25	MCD120-6 (2+2)	MCD120-14 (1+1)	N/A	N/A
MCST150	150	120÷150	16.7	58	25	MCD150-6 (3+3)	MCD150-14 (1+1)	N/A	N/A
MCST185	185	150÷85	19.2	64	25	MCD185-6 (3+3)	MCD185-14 (1+1)	N/A	N/A
MCST240	240	185÷240	21.1	75	15	MCD240-6 (3+3)	MCD240-14 (2+2)	N/A	N/A
MCST300	300	240	23.7	90	10	N/A	MCD300-14 (3+3)	N/A	N/A
MCST400	400	300	27.0	94	5	N/A	MCD400-14 (3+3)	MCD400-26 (2+2)	MCD400-60 (2+2)
MCST500	500	400	30.3	98	6	N/A	N/A	MCD500-26 (2+2)	MCD500-60 (2+2)
MCST630	600÷630	500	33.4	105	6	N/A	N/A	MCD630-26 (2+2)	MCD630-60 (2+2)
MCST800	800	600	38.0	112	3	N/A	N/A	N/A	MCD800-60 (2+2)
MCST1000	1000	800	44.0	120	3	N/A	N/A	N/A	MCD1000-60 (2+2)