


T&B Conduit Fittings

Portable Cord and Cable Fittings



Wiremesh grips support the following Liquidtight Cord Fittings Series.



2920 Series

2920AL Series



2516 Series

WMG-PC Series Wiremesh Grips for Portable Cord

T&B Wiremesh grips are ordered separately and fit with your existing inventory of Ranger™ fittings and liquidtight strain relief fittings. There's no need to duplicate inventory.

Application

- Provides high gripping strength for adequate cable support and strain relief without damage to the cable sheath
- Compression of a tapered neoprene bushing, assures the watertight integrity of the fittings

Cord and Cable Type

- S, SO, SV, ST, STD, SJ, SJO, SJT, SJTO, SVD

Features

- Prevents severe cord bends and pullouts
- Used in aluminum and/or steel fittings

How to select proper wiremesh grip:

1. Determine O.D. of portable cord e.g. .200
2. Determine size of knockout or threaded hub e.g. 1/2"

Material

Wiremesh made of stainless steel. Retaining rings made of aluminum.

Environment Classification

- Ordinary Locations

Range

.187 – 3.220



3. Select Cat. No. of strain relief fitting e.g. 2520, 2920AL.
4. Match up O.D. with grip range and strain relief to determine Cat. No. of Wiremesh Grip (e.g. .200 + 2520 = WMP-PC1)

Wiremesh Grips for Portable Cord



Cat. No.	Grip Range	Strain Relief Fitting							
		Straight		45°		90°		T&B Steel	T&B Steel
		Ranger™ Steel	Ranger™ Aluminum	T&B Steel	Ranger™ Malleable Iron	T&B Steel	Ranger™ Malleable Iron		
WMG-PC1	.187-.250	2920S	2920AL	2520	4920	2200	4960	4960AL	2267
WMG-PC2	.250-.375	2920S	2920AL	2521	4920	2201	4960	4960AL	2268
WMG-PC3	.375-.500	2921S	2921AL	2522	4921	2202	4961	4961AL	2269
WMG-PC4	.500-.625	2922S	2922AL	2524	4922	2204	4962	4962AL	2250
		2932S	2932AL	2534	4932	2209	4972	4972AL	2273
		2941S	2941AL	2544	4941	2214	4981	4981AL	2255
WMG-PC5	.625-.750	2922S	2922AL	2525	4922	2205	4962	4962AL	2251
		2932S	2932AL	2535	4932	2210	4972	4972AL	2274
		2941S	2941AL	2545	4941	2215	4981	4981AL	2256
WMG-PC6	.187-.250	2930S	2930AL	2530	4930	2206	4970	4970AL	2252
WMG-PC7	.250-.375	2930S	2930AL	2531	4930	2207	4970	4970AL	2271
				2541					
WMG-PC8	.375-.500	2931S	2931AL	2532	4931	2208	4961	4961AL	2272
		2940S	2940AL	2542	4940	2213	4980	4980AL	2254
WMG-PC9	.750-.875	2942S	2942AL	2536		2211			2253
				2546	4942	2216	4982	4982AL	2275
WMG-PC10	.875-1.000			2547		2217			2276
WMG-PC11	.875-1.000			2548		2218			2257
				2558		2220			2277
				2548		2218			2257
WMG-PC12	1.000-1.125			2558		2220			2277
				2549		2219			2258
				2559		2221			2278
WMG-PC13	1.125-1.250			2549			2258	2258	2219
				2559		2221			2278
				2556			2279	2279	2222
WMG-PC14	1.125-1.250			2563		—			2282
				2564		—			2283
WMG-PC15	1.250-1.375			2256		2222			2279
WMG-PC16*	1.375-1.500			2564		—			2283
				2557		2223			2280
WMG-PC17*	1.125-1.250			2573		—			2284

Cat. No.	Grip Range	Strain Relief Fitting	
		Straight T&B Steel	90° T&B Steel
WMG-PC18*	1.250-1.375	2573	2284
WMG-PC19*	1.375-1.500	2565	2285
		2574	
WMG-PC20*	1.500-1.625	2565	2285
		2574	
WMG-PC21*	1.625-1.750	2575	2286
WMG-PC22*	1.750-1.875	2575	2286

*Replacement Gland Nut Supplied With These Catalogue Numbers only