



T&B Conduit Fittings

Liquidtight Flexible Metal Conduit Fittings



Fittings for Liquidtight flexible metal conduit with metric threads of ISO Form (BS-4568-SA BS 162).

ISO Metric Thread Liquidtight Fittings*

Cat. No.	Flexible Conduit Size	Metric ISO Thread	Dimensions (mm)		
			A	B	C
Nylon insulated straight fittings					
9330	1/4"	16	36	21	12
9331	1/4"	20	36	21	12
9306	5/16"	16	36	26	12
9360	3/8"	16	40	29	16
9361	3/8"	20	40	29	16
9362	1/2"	20	42	35	16
9363	3/4"	25	45	42	16
9364	1"	32	54	47	23
Nylon insulated 45° angle fittings					
9340	3/8"	16	27	29	16
9341	3/8"	20	27	29	16
9342	1/2"	20	27	35	16
9343TB	3/4"	25	31	42	16
9344	1"	32	34	47	23
Nylon insulated 90° angle fittings					
9350	3/8"	16	35	29	16
9351	3/8"	20	35	29	16
9352TB	1/2"	20	39	35	16
9353TB	3/4"	25	43	42	16
9354TB	1"	32	48	47	23

U.L. Listed Liquidtight.




Fig. 1




Fig. 2




Fig. 3

Mechanical adapter with internal threads to mate with NPT threaded fittings and MS type fittings.

Material: aluminum

NPT/MS Fitting Adaptors



Cat. No.	N.P.T. Thread	AN-MS Fitting Shell Size	Thread Size	Dimensions (in.)		
				A	Fig.	B
MSA05014	1/2"	14, 14S	3/4-20 UNEF-2B	1.000	1	1.175
MSA05016	1/2"	16, 16S	7/8-20 UNEF-2B	1.000	2	1.175
MSA05018	1/2"	18	1-20 UNEF-2B	1.125	3	1.175
MSA07516	3/4"	16, 16S	7/8-20 UNEF-2B	1.250	1	1.356
MSA07518	3/4"	18	1-20 UNEF-2B	1.250	1	1.300
MSA07520	3/4"	20, 22	1-3/16-18 UNEF-2B	1.375	3	1.300
MSA10020	1	20, 22	1-3/16-18 UNEF-2B	1.500	1	1.431
MSA10024	1	24, 28	1-7/16-18 UNEF-2B	1.625	3	1.313
MSA10032	1	32	1-3/4-18 UNS-2B	2.000	3	1.576
MSA10036	1	36	2-18 UNS-2B	2.250	3	1.738

Not CSA Certified.