

EZ Klik™ locking mechanism



Self-Aligning Solid Contacts

- Self-aligning Nickel plated full-round pins and sleeves for maximum cool contact area.
- Sleeve pressure rings ensure constant surface contact force.
- Nickel plating offers maximum corrosion resistance for any use.

Screw Collars Stay Put

Turreted grip allows for easy handling.

The Easy Way

EZ Klik™ locking feature on all 20/30A plugs and connectors.

75% Faster Cable Assembly EZ Tite™ System

- One-piece cable gland.
- Nylon locking screw prevents loosening.
- Easy hand assembly of cable gland, Grip Tite™ 6-Finger clamp and onion-ring bushing.

Safe Connections Standard

Ground contacts make first, break last for safe connections even under load.

Combination Flap/Screw Cover

- Integral neoprene gasket for IP67 Watertight protection.
- Standard flap cover for IP44 Splashproof protection.
- Unique flex hinge design.

Neoprene Cable Bushing

- Onion ring design.
- Universal fit capability.

Solid Neoprene Gasket In Handle

Grip Tite™ 6-Finger Clamp

Provides superior cable retention.

Secure Grip Handle

- Tapered shoulder (20 and 30A).
- Ribbed shoulder (60 and 100A).

Raised Ground Terminal

Ensures safe connections every time.

Fast and Easy Wiring

- Unique, one-way terminal access.
- Clearly marked terminal connections.

Double Secure Wiring

Dual, combination point terminal screws for failsafe connections.

Standard Interface / World Ready Full International Compliances

EN60309

UL Classification to IEC 309-1 and IEC 309-2.

cULus Listing: UL 1682/1686 and CSA C22.2 No. 182.1.

CE conforms to EC Low Voltage Directive.

North American and Global Voltage Polarization "clock positions" available in all standard ratings.



Safe Voltage Selections

One-Piece contact carriers with Full-Colour IEC standard voltage-phasing. Coding ensures correct product application every time.

Features



No Tools, No Screws Necessary

- EZ Klik™ locking handle saves 75% on assembly time.
- Unique EZ Klik™ assembly feature on 20 and 30 Amp plugs and connectors makes installation and inspection fast and reliable.
- Captured gaskets in handles seal out water, chemicals and dust.




Easy Action Single-Wiring Point Access Saves Time Wiring

- All terminal screws face in same direction allowing installer to make safe and secure conductor terminations in 30% less time than other devices.
- Rugged, corrosion free thermoplastic housings are colour-coded for safe and reliable connections to all other mating type/polarizations, with raised ground terminal standard.




Simple Cable Clamping

- Threaded EZ Tite™ cable gland on 20 and 30 Amp devices makes assembly fast and easy.
- One-piece lock screw clamps locking hold, with no external metal contact possible. (20 and 30 Amp devices)




Unique Fast Assembly

- One-piece EZ Tite™ cable gland with locking screw loads to cable followed by Grip Tite™ 6-Finger cable clamp/grip piece.
- Watertight onion ring bushing fits a wide variety of outside diameters.



Watertight and Grip Tite™ Safety

- Grip Tite™ flexible 6-finger clamp teeth holds well beyond all agency test pullout forces.
- No internal clamps required.
- Available in all amperages.



The Performance Connection

- Watertight spring-loaded covers with high-strength flex-hinge screw covers on IP67 devices.
- Flap covers on IP44 splashproof styles.
- Safety, performance and durability for all IEC 309 applications worldwide.

