

Sealants and Lubricants

Type CT — CONTAX™ Oxide Inhibiting Coumpound

- Seals electrical connections from oxygen and moisture
- Non-water soluble, non-petroleum based polymer grease
- Nontoxic, will not irritate the skin
- Service temperature to 238 °C (460 °F) can be applied in -18 °C (0 °F) weather



Cat. No.	Description
CTA	1/2 oz. Package
CTB	4 oz. Plastic Bottle
CTB8	8 oz. Plastic Bottle
CTQ	Quart Can
CTG	Gallon Can

Type WW — Wire Bristle Brush

- Removes oxides from conductor surfaces
- Easy-grip handle with guard to prevent rubber-glove puncture
- Replaceable long-life brushes can be rotated
- Handle and guard coated with durable, nonconductive plastic for safety



Cat. No.	Description	Pkg. Qty
WWB1	Complete Brush with Handle	1
WRB1	Brush Replacement	

Sealants and Lubricants

Type DX — Duct Seal

- Seals around junction boxes, flashings, service mast entries, service cable entries and countless other applications
- Easy to use, forms around irregular surfaces and configurations
- Highly resistant to cracking, drying and shrinking
- Cuts and trims easily
- Can be painted immediately after application
- Grey colour
- No unpleasant odor
- -6.7 °C to 100 °C (20 °F to 212 °F) workable temperature range
- -40 °C to 121 °C (-40 °F to 250 °F) service temperature range
- Contains no asbestos



Cat. No.	Description
DX-1	1 lb Slug
DX-5	5-1 lb Slugs
DX-5S	5 lb Slug

U.L. Classified R13335.



Silicone Lubricant for High Voltage Electrical Work

Cat. No.	Description	Pkg. Qty
2012	2 grams	250 tubes
2015	5 grams	100 tubes
SL5	5 oz./142 grams	12 tubes

