

## Ocal-Blue double-coat FS and FD series covers




Designed for use with Ocal FS and FD series boxes



### Ocal-Blue double-coat FS and FD series covers

Cat. No.	Description	Material
<b>Single-gang</b>		
DS23- <u>  </u>	Duplex Receptacle Cover	Steel
DS21G- <u>  </u>	Round Flush Receptacle Cover	Iron
DS32G- <u>  </u>	Toggle Switch Cover	Iron
DS100G- <u>  </u>	Blank Cover	Aluminum
<b>Single-gang — NEMA 3R Raintight when used with appropriate Ocal boxes</b>		
CWPDR-FS-G- <u>  </u>	Duplex Receptacle Cover – Box Mount – Horizontal	Aluminum
CFSDR-G- <u>  </u>	Duplex Receptacle Cover – Box Mount – Vertical	Aluminum
CFSHG-G- <u>  </u>	GFCI Receptacle Cover – Box Mount – Horizontal	Aluminum
CFSRG-G- <u>  </u>	GFCI Receptacle Cover – Box Mount – Vertical	Aluminum
DS185- <u>  </u>	Front Lever Switch Cover – Box Mount – NEMA 4	Aluminum
<b>Double-gang</b>		
S1002G- <u>  </u>	Blank Cover	Iron
S322G- <u>  </u>	2-Toggle Switch Cover	Iron
S232- <u>  </u>	2-Duplex Receptacle Cover	Stamped Steel
S232GFI- <u>  </u>	2-GFCI Receptacle Cover	Steel
<b>Double-gang — NEMA 3R Raintight when used with appropriate Ocal boxes</b>		
DS1282- <u>  </u>	2-Plunger-Style Switch Cover	Aluminum

PVC-coated covers in other styles and materials are available upon request. Contact Technical Services for more information.

Cat. No.	Colour
<b>DS23-</b>	
<u>  </u>	<b>= space for color identifier</b>
<u>  </u> G =	Gray 
<u>  </u> W =	White 
<u>  </u> B =	Blue 
Custom colors also available.	

## Ocal-Blue double-coat conduit unions



Explosion-proof, dust-ignition-proof three-piece couplings



### Product features

- Install in threaded thick-wall conduit systems in hazardous areas
- Use UNY male unions to connect conduit to a conduit fitting, junction box or device enclosure
- Use UNF female unions to connect conduit to conduit or to provide means for future modifications to the conduit system
- Nominal .002" (2 mil) blue urethane on interior and exterior
- Nominal .040" (40 mil) PVC coating bonded to exterior
- Pressure-sealing sleeves protect your connection
- Explosion-proof, dust-ignition-proof and suitable for use in the following environments:<sup>†</sup>
  - Class I, Divisions 1 & 2, Groups A, B, C, D
  - Class II, Division 1, Groups E, F, G
  - Class III, Divisions 1 & 2



### UNY male unions

	Cat. No.	Pipe Size (in.)	Metric Size Designator*	Overall Length		Overall Dimensions	
				(in.)	(mm)	(in.)	(mm)
	UNY105- <u>  </u>	1/2	16	2.39	60.71	1.50	38.10
	UNY205- <u>  </u>	3/4	21	2.44	61.98	1.81	45.97
	UNY305- <u>  </u>	1	27	2.75	69.85	2.00	50.80
	UNY405- <u>  </u>	1 1/4	35	3.06	77.72	2.75	69.85
	UNY505- <u>  </u>	1 1/2	41	3.63	92.20	3.06	77.72
	UNY605- <u>  </u>	2	53	3.50	88.90	3.81	96.77
	UNY705- <u>  </u>	2 1/2	63	4.81	122.17	4.31	109.47
	UNY805- <u>  </u>	3	78	5.34	135.64	5.06	128.52
	UNY905- <u>  </u>	3 1/2	91	5.50	139.70	5.69	144.53
	UNY1005- <u>  </u>	4	103	5.63	143.00	6.19	157.23
	UNY012- <u>  </u>	5	129	5.25	133.35	8.19	208.03
	UNY014- <u>  </u>	6	155	5.38	136.65	9.31	236.47

UNY Male 1/2"-4"  
(shown uncoated)

UNY Male 5"-6"  
(shown uncoated)

### UNY female unions

	Cat. No.	Pipe Size (in.)	Metric Size Designator*	Overall Length		Overall Dimensions	
				(in.)	(mm)	(in.)	(mm)
	UNF105- <u>  </u>	1/2	16	1.88	47.75	1.50	38.10
	UNF205- <u>  </u>	3/4	21	2.13	54.10	1.81	45.97
	UNF305- <u>  </u>	1	27	2.16	54.86	2.00	50.80
	UNF405- <u>  </u>	1 1/4	35	2.25	57.15	2.75	69.85
	UNF505- <u>  </u>	1 1/2	41	2.75	69.85	3.06	77.72
	UNF605- <u>  </u>	2	53	2.50	63.50	3.81	96.77
	UNF705- <u>  </u>	2 1/2	63	3.50	88.90	4.31	109.47
	UNF805- <u>  </u>	3	78	4.00	101.60	5.06	128.52
	UNF905- <u>  </u>	3 1/2	91	4.16	105.66	5.69	144.53
	UNF1005- <u>  </u>	4	103	4.25	107.95	6.19	157.23
	UNF012- <u>  </u>	5	129	3.81	96.77	8.19	208.03
	UNF014- <u>  </u>	6	155	3.81	96.77	9.31	236.47

\* Metric size designator (ANSI C80.1-1994). † Ratings prior to PVC coating.

Cat. No. Colour

### UNF105-

   = space for color identifier

G = Gray 

W = White 

B = Blue 

Custom colors also available.